



Product Service

CERTIFICATE

No. Z1A 090361 0051 Rev. 00

Holder of Certificate: **Kinnarps AB**

Industrigatan 1
521 88 Kinnarp
SWEDEN

Certification Mark:



Product:

**Office chairs
for user weight up to 130 kg**

Tested according to:

DIN 4573:2021
DIN EN 1335-1:2023
DIN EN 1335-2:2019
PPP 51960D:2023
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713342408

Valid until: 2030-10-27

Date, 2025-10-29

(Michael Weber)

CERTIFICATE

No. Z1A 090361 0051 Rev. 00

Model(s): **Espera**
(D-1061-DR, D-1061-DRLF, D-1061-DRLM,
D-1061-D, D-1061-DLF, D-1061-DLM,
D-1061-DG, D-1061-DGLF, D-1061-DGLM)

Parameters:

General description	Seat height adjustment by gas pressure lift. Combinations with standard range gas lift fulfill requirements for type A, combinations with 3D armrest fulfill requirements for type B, all further combinations fulfill requirements for type Ax according to DIN EN 1335-1:2023.
Seat	Upholstered with plastic structure on bottom side
Gas lift	STAB-O-MAT D Base Material: 010618, outside diameter: 28 mm, Wall thickness: 2.5 mm, strength Class: 4
Seat height	400 - 580 mm ($\Delta=180$ mm - extended range for type Ax) / 400 - 540 mm ($\Delta=140$ mm - standard range for type A)
Backrest	Fabric back Relaxoflex (DR, DRLF, DRLM) / Fabric back (D, DLF, DLM) / Mesh back (DG, DGLF, DGLM)
Lumbar support	1D Basic / 2D Comfort
Armrest (optional)	Without (DR, D, DG) / 3D - adjustable in height, depth and width (DRLF, DLF, DGLF) / 4D - adjustable in height, depth, width and angle (DRLM, DLM, DGLM)
Base	Polymer (A10) Aluminum (A16, A41, A33)
Castors	Castors with load-dependent brake system \varnothing 60 mm for soft or hard floors